



SINNY

TC3 Series





规格

SPECIFICATIONS

电源电压 Power supply	① 100-240VAC/DC ② 24VAC/DC	
允许电压变动范围 Allowable voltage range	电源电压的90-110% 90-110% of rated voltage	
消耗功率 Power consumption	≤ 8VA	
输入类型 Input type	热电偶 TC	K E J N T S R B
	热电阻 RTD	Pt100 Cu50
	线性电流 Linear current	0-20mA 4-20mA
	线性电压 Linear voltage	0-5V 1-5V
显示精度 Display accuracy	±0.5%	
输出类型 Output type	继电器 Relay	250VAC-3A 30VDC $\overline{\overline{=}}$ 3A 一开一闭 250VAC-3A 30VDC $\overline{\overline{=}}$ 3A 1NO 1NC
	SSR	12VDC $\overline{\overline{=}}$ $\pm 2V$, ≤20mA
	电流 Current	DC 4-20mA 或 DC 0-20mA, 阻性负载: ≤ 500Ω DC 4-20mA or DC 0-20mA, Load resistance: ≤ 500Ω
	电压 Voltage	DC 0-10V 或 DC 1-10V DC 0-10V or DC 1-10V
报警输出 Alarm output	继电器 Relay	AL1: 250VAC-3A 1开 AL1: 250VAC-3A 1NO
选项输出 Option output	RS485通信 RS485 Comm.	Modbus RTU
控制方式 Control type	位式控制、PID控制 ON/OFF、PID Control	
采样周期 Sampling period	100ms	
继电器寿命 Relay life cycle	机械 Mechanical	≥250万次 ≥2,500,000 operations
	电气 Electrical	≥10万次 (阻性负载: 250VAC~3A) ≥100,000 operations (resistance load: 250VAC~3A)
耐压 Dielectric strength	端子和外壳间: 3000 VAC ~ 50/60 Hz 1分钟 Between all terminals and case: 3000VAC ~ 50/60Hz for 1 min	
耐振动 Vibration	5-55Hz (周期1分钟) 振幅0.75mm X,Y,Z各方向2小时 0.75mm amplitude at frequency 5 to 55Hz (for 1 min.) in each X,Y,Z direction for 2 hours	
绝缘阻抗 Insulation resistance	≥100MΩ (500VDC $\overline{\overline{=}}$ megger)	
抗干扰 Noise immunity	由于扰模拟器产生的方波干扰 (脉宽1μs) ±2KV R相, S相 ±2kv square shaped noise (pulse width 1μs) by noise simulator R-phase, S-phase	
停电记忆 Memory retention	≈10年 (非易失性半导体存储方式) ≈10 years (non-volatile semiconductor memory type)	
使用环境温度 Ambient temp.	-10 ~ 50°C 存储时: -20 ~ 60°C (未结冰, 未结露状态) -10 ~ 50°C storage: -20 ~ 60°C (no freezing or condensation)	
使用环境湿度 Ambient humi.	35% ~ 85%RH 存储时: 35% ~ 85%RH (未结冰, 未结露状态) 35% ~ 85%RH storage: 35% ~ 85%RH (no freezing or condensation)	

型号

MODEL

TC	□	-	□	-	□	-	□	*	□
通讯输出 Com. output	无内容(Blank)		无通讯(NO RS485 function)		C		RS485通讯(Modbus RTU) RS485 Communication output (Modbus RTU)		
电源电压 Power supply	2		100-240VAC/DC		4		24VAC/DC		
输入类型 Input type	G		TC(K E J N T S R B) RTD(Pt100 Cu50) mA(0-20mA 4-20mA) V(0-5V 1-5V)						
报警输出 Alarm output	1		一路报警(One alarm)						
输出类型 Output type	W		Relay继电器触点/SSR驱动输出(Relay contact/SSR drive output)						
	1U		电压控制输出(Voltage controlled output)						
	2U		温度变送电压输出(Temperature variable voltage output)						
	1A		电流控制输出(Current controlled output)						
	2A		温度变送电流输出(Temperature variable current output)						
外型尺寸 Size	S		W48×H48mm						
	H		W48×H96mm						
	M		W72×H72mm						
	L		W96×H96mm						
产品类型 Product type	3		系列代号(Series code)						
项目名称 Item	TC		温度控制器(Temperature controllers)						

尺寸

SIZE

型号 Model	外形尺寸(宽*高*深) mm Dimensions (W*H*D)	开孔尺寸(宽*高) mm Cut-out size (W*H)	装箱数 PCS / CTN
TC3-S	48*48*75	45*45	50
TC3-H	48*96*75	45*92	50
TC3-M	72*72*75	68*68	50
TC3-L	96*96*75	92*92	50